

Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 07.12.2020 / 0016
Replacing version dated / version: 22.02.2019 / 0015
Valid from: 07.12.2020
PDF print date: 27.05.2021
Diesel - Bactericide
1 | Art.: 6750 7028, Art.: 6754 7028

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Diesel - Bactericide

1 | Art.: 6750 7028, Art.: 6754 7028

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Biocide

Fuel additive

Sector of use [SU]:

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

1.3.1 Innflytjandi

AB varahlutir.
Funahöfða 9, 110 Reykjavík
+354 567 60 20
ab@ab.is, www.ab.is

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Neyðarsímanúmer:

Eitrunarmiðstöð Landspítali, + 354 543 22 22

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	3	H226-Flammable liquid and vapour.
Acute Tox.	4	H332-Harmful if inhaled.
Acute Tox.	4	H312-Harmful in contact with skin.
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	1B	H350-May cause cancer.
Muta.	2	H341-Suspected of causing genetic defects.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H226-Flammable liquid and vapour. H332-Harmful if inhaled. H312-Harmful in contact with skin. H319-Causes serious eye irritation. H315-Causes skin irritation. H350-May cause cancer. H341-Suspected of causing genetic defects. H412-Harmful to aquatic life with long lasting effects.

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.
 P308+P313-IF exposed or concerned: Get medical advice / attention.

Restricted to professional users.
 Xylene
 3,3'-Methylenebis[5-methyloxazolidine]

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 Hydrocarbons can be harmful to water.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	601-022-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	215-535-7
CAS	1330-20-7
content %	80-100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315

Propan-2-ol	
Registration number (REACH)	---
Index	603-117-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	200-661-7
CAS	67-63-0
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Page 3 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

3,3'-Methylenebis[5-methyloxazolidine]	
Registration number (REACH)	---
Index	612-290-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	266-235-8
CAS	66204-44-2
content %	2,76
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam. 1, H318 Carc. 1B, H350 Muta. 2, H341 Acute Tox. 3, H311 STOT RE 2, H373 (respiratory tract, gastrointestinal tract) Skin Sens. 1A, H317 Aquatic Chronic 2, H411 Skin Corr. 1B, H314

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Do not feed fats, oils or milk.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Skin contact:

Product removes fat.

Dermatitis (skin inflammation)

Skin resorption

Inhalation:

Oedema of the lungs

Ingestion:

Gastrointestinal disturbances

Nausea

Vomiting

Danger of aspiration.

Lung damage

After resorption:

(GB)

Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2020 / 0016

Replacing version dated / version: 22.02.2019 / 0015

Valid from: 07.12.2020

PDF print date: 27.05.2021

Diesel - Bactericide

1 | Art.: 6750 7028, Art.: 6754 7028

Headaches

Fatigue

Dizziness

Euphoria

Cramps

Narcotic effect.

Liver and kidney damage

Effects/damages the central nervous system

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Ingestion:

Activated carbon

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Foam

Extinguishing powder

CO₂**Unsuitable extinguishing media**

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

Danger of explosion.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Use no flammable substances.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

GB

Page 5 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid inhalation of the vapours.
 Ensure good ventilation.
 If applicable, suction measures at the workstation or on the processing machine necessary.
 Keep away from sources of ignition - Do not smoke.
 Take precautions against electrostatic charges.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep locked away.
 Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Do not store with flammable or self-igniting materials.
 Solvent resistant floor
 Observe special storage conditions.
 Store in a well ventilated place.
 Protect from direct sunlight and warming.
 Unsuitable container:
 Various plastics
 Rubber
 Light metals

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Xylene	Content %:80-100
WEL-TWA: 220 mg/m ³ (50 ppm) (WEL), 50 ppm (221 mg/m ³) (EU)	WEL-STEL: 100 ppm (441 mg/m ³) (WEL), 100 ppm (442 mg/m ³) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Xylene 10/a (67 33 161) - Compur - KITA-143 SA (550 325) - Compur - KITA-143 SB (505 998) - INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004) - NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999 	
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)	


Chemical Name	Propan-2-ol	Content %:1-<5
WEL-TWA: 400 ppm (999 mg/m ³)	WEL-STEL: 500 ppm (1250 mg/m ³)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Alcohol 25/a i-Propanol (81 01 631) - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - NIOSH 1400 (ALCOHOLS I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - Draeger - Alcohol 100/a (CH 29 701) 	

Page 6 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

BMGV: ---	Other information: ---
-----------	------------------------

Xylene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg	
	Environment - soil		PNEC	2,31	mg/kg	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, marine		PNEC	12,46	mg/kg	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg	

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg dw	
	Environment - sediment, marine		PNEC	552	mg/kg dw	
	Environment - soil		PNEC	28	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
	Environment - oral (animal feed)		PNEC	160	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	319	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	89	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	888	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	500	mg/m3	

 WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).

Page 7 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 07.12.2020 / 0016
Replacing version dated / version: 22.02.2019 / 0015
Valid from: 07.12.2020
PDF print date: 27.05.2021
Diesel - Bactericide
1 | Art.: 6750 7028, Art.: 6754 7028

(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Solvent resistant protective gloves (EN 374).
Recommended
Protective nitrile gloves (EN 374).
Protective Viton® / fluoroelastomer gloves (EN 374).
Minimum layer thickness in mm:
0,4 - 0,5
Permeation time (penetration time) in minutes:
>= 240 - >= 480
Protective hand cream recommended.
Unsuitable material:
Rubber gloves (EN 374).
Leather gloves.
Protective Neoprene® / polychloroprene gloves (EN 374).
Protective PVC gloves (EN 374).

Skin protection - Other:
Solvent resistant protection clothing (EN 13034)
According to operation.
Protective working garment, antistatic (EN1149)
Low inflammability protective clothing.

Respiratory protection:
If OES or MEL is exceeded.
Gas mask filter A (EN 14387), code colour brown
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
Not applicable

Additional information on hand protection - No tests have been performed.
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
Selection of materials derived from glove manufacturer's indications.
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Transparent
Odour:	Aromatic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	135-145 °C
Flash point:	24 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	1 Vol-% (Xylene)
Upper explosive limit:	7 Vol-% (Xylene)
Vapour pressure:	10 hPa (20°C, Xylene)
Vapour density (air = 1):	Not determined
Density:	0,87 g/cm ³ (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	3,12 (References Xylene, Log Pow)
Auto-ignition temperature:	~460 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	>7 mm ² /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Electrostatic charge

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Diesel - Bactericide

1 | Art.: 6750 7028, Art.: 6754 7028

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	1714	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	1,6	mg/l/4h			calculated value, Aerosol
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Xylene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2840	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>1700	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	21,7	mg/l/4h	Rat		Vapours, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Symptoms:						breathing difficulties, drying of the skin., drowsiness, unconsciousness, burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea

Propan-2-ol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	12800-13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	5000	ppm	Rat		Vapours OECD 451

3,3'-Methylenebis[5-methyloxazolidine]

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	630-900	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	760	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	2	mg/l/4h	Rat	OECD 436 (Acute Inhalation Toxicity - Acute Toxic Class Method)	Mist, Dust
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Corrosive
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Corrosive
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative, Does not conform with EU classification.

Page 11 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

Specific target organ toxicity - repeated exposure (STOT-RE):							Positive, Target organ(s): gastrointestinal tract, Target organ(s): respiratory system
---	--	--	--	--	--	--	--

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Diesel - Bactericide 1 Art.: 6750 7028, Art.: 6754 7028							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.3. Bioaccumulative potential:							Concentration in organisms possible.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.

Xylene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	86	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	8,2	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	24h	75,5	mg/l	Daphnia magna		
12.1. Toxicity to algae:	IC50	72h	10	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		>3				
12.3. Bioaccumulative potential:	BCF		0,6-15				

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC10	16h	1050	mg/l	Pseudomonas putida		
12.3. Bioaccumulative potential:	BCF		3,2				Low
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		

GB

Page 12 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Slight
12.4. Mobility in soil:	Koc		1,1				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

3,3'-Methylenebis[5-methyloxazolidine]							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Kow		-0,3			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	
12.1. Toxicity to algae:	EC50	72h	5,7	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 07 04 04 other organic solvents, washing liquids and mother liquors
 13 07 03 other fuels (including mixtures)
 14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Approved rubbish dump for special refuse
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

GB

Page 13 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

Residues may present a risk of explosion.
 Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

14.1. UN number: 1993

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name: UN 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, ISOPROPYL ALCOHOL)
 14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 Classification code: F1
 LQ: 5 L
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code: D/E



Transport by sea (IMDG-code)

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (XYLENES, ISOPROPYL ALCOHOL)
 14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 EmS: F-E, S-E
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name: Flammable liquid, n.o.s. (XYLENES, ISOPROPYL ALCOHOL)
 14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 844 g/l

Page 14 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 07.12.2020 / 0016
 Replacing version dated / version: 22.02.2019 / 0015
 Valid from: 07.12.2020
 PDF print date: 27.05.2021
 Diesel - Bactericide
 1 | Art.: 6750 7028, Art.: 6754 7028

Observe Regulation (EU) No 528/2012 concerning the placing of biocidal products on the market.
 Additional data acc. to Art. 69 (2), Regulation (EU) No 528/2012 (Biocide products):
 The identity of every active substance and its concentration in metric units:
 3,3'-Methylenebis[5-methyloxazolidine]
 2,76 g/100 g
 The uses:
 Slimicide
 Registration number BAuA (Federal Institute for Occupational Health and Safety, Germany): baua:Reg.-Nr. N-36176
 Biocidal product authorisation number (Regulation (EU) No. 528/2012):
 n.d.a.

Observe incident regulations.

Observe regulations on prohibition of chemicals.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
Acute Tox. 4, H332	Classification according to calculation procedure.
Acute Tox. 4, H312	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 1B, H350	Classification according to calculation procedure.
Muta. 2, H341	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H350 May cause cancer.

Flam. Liq. — Flammable liquid
 Acute Tox. — Acute toxicity - inhalation

Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2020 / 0016

Replacing version dated / version: 22.02.2019 / 0015

Valid from: 07.12.2020

PDF print date: 27.05.2021

Diesel - Bactericide

1 | Art.: 6750 7028, Art.: 6754 7028

Acute Tox. — Acute toxicity - dermal

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

Muta. — Germ cell mutagenicity

Aquatic Chronic — Hazardous to the aquatic environment - chronic

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Acute Tox. — Acute toxicity - oral

Eye Dam. — Serious eye damage

STOT RE — Specific target organ toxicity - repeated exposure

Skin Corr. — Skin corrosion

Förch SAS
ZAE Le Marchais Renard
CS 50125 Montereau-sur-le-Jard
77019 Melun Cedex
Frankreich
Tel. +33 1 64 14 48 48
Fax. +33 1 64 14 48 49
E-Mail: info@forch.fr
Internet: www.forch.fr

Förch SAS
17 rue de Marbourg
9764 MARNACH
Luxemburg
Tel. +352 269 03267
Fax +352 269 03368
E-Mail: info@forch.fr
Internet: www.forch.fr

S.C. Foerch S.R.L.
Str. Zizinului nr.110
500407 Brasov
Rumänien
Tel. +40 368 408192
Fax. +40 368 408193
E-Mail: info@foerch.ro
Internet: www.foerch.ro

Foerch AG
Muttenerstrasse 143
4133 Pratteln
Schweiz
Tel. +41 61 8262031
Fax. +41 61 8262039
E-Mail: info@foerch.ch
Internet: www.foerch.ch

Foerch Bulgaria EOOD
22 Parva Balgarska Armija Blvd.
1225 Sofia, Bulgarien
Tel. 00359 2 981 2841
Fax. 00359 982 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
Spanien
Tel. +34 958 40 17 76
Fax. +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
Seinhuisstraat 5 B4
Poort 0331
3600 Genk
Belgien
Tel. +32 89 71 66 61
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Ziebe Limited
7 Century Court, Westcott,
Aylesbury, Bucks, HP18 0XP (UK)
Grossbritannien
Tel +44 12 96 65 52 82
E-Mail: sales@ziebe.co.uk
Internet: www.ziebe.co.uk

SKY NORD
Sofia Kovalevskaya ul.
D.1, ST.2, K.1
RUS 127247 MOSCOW
Russland
E-Mail: skynord.office@gmail.com

Förch Polska Sp. z o.o
Międzyrzecze Górne 379
43-392 K/Bielska-Bialej
Polen
Tel. +48 338196000
Fax. +48 338158548
E-Mail: info@forch.pl
Internet: www.forch.pl

Vardalis SM P.C.
Ethnikis Antistasis 62
57007 Chalkidona-Thessaloniki
Griechenland
Tel. +30 23910 21222
Fax. +30 23910 21223
E-Mail: info@forch.gr
Internet: www.forch.gr

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
Ungarn
Tel. +36 22 348348
Fax. +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.r.l.
Via Antonio Stradivari 4
39100 Bolzano (BZ)
Italien
Tel: +39 0471 204330
Fax: +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Demmersweg 18
7556 BN Hengelo
Niederlande
Tel. +31 85 77 32 420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

AB varahlutir ehf
Funahöfði 9
110 Reykjavík
Tel. +354 567 6020
E-mail: ab@ab.is
Internet: www.ab.is

Förch Slovensko s.r.o.
Rosinská cesta 12
010 08 Žilina
Slowakei
Tel +421 41 5002454
E-Mail: info@forch.sk
Internet: www.forch.sk

Förch Sverige AB
Brännarevägen 1
151 55 Södertälje
Schweden
Tel. +46 855089264
E-mail: info@foerch.se
Internet: www.foerch.se

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhřetěves
Tschechien
Tel. +420 271 001 984-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

FORCH d.o.o.
Ljubljanska cesta 51A
1236 Trzin
Slowenien
Tel. +386 1 2442490
Fax. +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
Gnangara WA 6077
Tel. +61 (08) 9303 9113
Fax. +61 (08) 9303 9114
Emergency telephone: +614 13 550 330
Email : sales@forch.com.au
Internet: www.forch.com.au

Troscoe Ltd
Unit 6, 13 Highbrook Drive
East Tamaki 2013, New Zealand
Tel: +64 21 081 30780 / +64 21 024 05583
Email:sales@forchnz.co.nz
Internet: www.forchnz.co.nz

Förch Portugal Lda
Rua República da Bolivia No. 69, 1 esq
1500-544 Lisboa
Portugal
Tel. +351 917314442
E-Mail: info@forch.pt
Internet: www.forch.pt

Trigers SIA
Straupes iela 3
1073 Riga
Lettland
Tel. +371 6 7 90 25 15
Fax. +371 67 90 24 96
E-Mail: trigers@trigers.lv
Internet: www.trigers.lv

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Şti.
Haramidere Mevkii Beysan Sanayi
Sitesi Birlik Caddesi No:6/3
34524 Beylikdüzü / Istanbul
Türkei
Tel. +90 (0)212 422 8744-45
Fax. +90 (0)212 422 8788
E-Mail: info@forch.com.tr
Internet: www.forch.com.tr

Total Consumables Ltd
Coolnafearagh
Monasterevin
Co. Kildare
W34 TX29
Irland
Tel. +353871271473

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.12.2020 / 0016

Replacing version dated / version: 22.02.2019 / 0015

Valid from: 07.12.2020

PDF print date: 27.05.2021

Diesel - Bactericide

1 | Art.: 6750 7028, Art.: 6754 7028

CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCRID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.